

TECHNICAL DATASHEET		
EGGER PRO LAMINATE FLOORING		12/33 Classic
Coreboard	E1 HCHO	HDF swell stopp plus
Profile	UNI Fit Patented	The patented UNI fit! installation system stands for a quick and simple installation process without glue. Produced under the licence of Flooring Industries™.
Guarantee domestic area	25 years	according to Egger Guarantee
Guarantee comercial area	5 years	according to Egger Guarantee
Antistatic properties according EN1815	⚡	yes, < 2 kV
Class of use	33	
European Norm EN13329	EN 13329-33	
Format	CLASSIC	
Dimension mm (length x width)	1291 x 193	
Complete thickness	12	
Thickness of silenzio® special cellulose		
Bevel	WV4	
Pallet	Packaging One-way-pallet	
Paket information		
	Piece	6
	m ²	1,49
	kg	16,31
Pallet information		
	Piece	312
	m ²	77,74
	kg	860,00
Classification and general requirements according EN13329		
Abrasion resistance according EN13329, annex E	AC5 (IP ≥ 6000)	
Impact resistance according EN13329, annex H	Big ball: ≥ 1000 mm Small ball: ≥ 15 N	
Resistance to staining EN438	Group 1 + 2: level 5 group 3: level 5	
Effect of furniture leg according EN424	No damage shall be visible, when tested with foot Type 0 artefact	
Effect of a castor chair according EN425 (Type W)	No change in appearance or damage	
Thickness swelling according ISO 24336	≤ 18 %	
Tolerance of top layer according EN13329	length ± 0,5 mm width ± 0,1 mm thickness ± 0,5 mm	
Light fastness according EN13329	grey scale ≥ level 4 (EN:20105-A02)	
Static indentation by constant pressure according EN ISO 24343-1	< 0,05	
Surface soundness according EN13329, annex D	≥ 1,0 N/mm ²	
Thermal resistance according to EN 12667	0,09 m ² K/W	

